



**OKIMED103 – Floralabels Luggage tag (4 per sheet)
Premium Grade #4161**

Media Warranty Statement

OKI Reference : OKIMED103

Media : Floralabels Luggage tag (4 per sheet) Premium Grade #4161

Device : C824n, C824dn, C834nw, C834dnw, C844dnw

1. Media Statement Summary

This document provides information on how the device mentioned below (“Printer”) must be set up and used when printing on the media specified (“Media”). The conditions of use detailed in Section 2 must be followed to obtain the best Print Quality with the Media & Printer combination.

- Printer:
 - Models: C824n, C824dn, C834nw, C834dnw, C844dnw
 - Firmware Level: FW Suite A01.17_0_4 or later
- Media:
 - Manufacturer : Floralabels
 - Name : Luggage tag (4 per sheet) Premium Grade
 - Reference # : #4161
 - Lot # or Date : N/A
 - Size tested : A4
 - Cut : No

2. Conditions of Use

2.1. Summary

The conditions of use specified in this section must be adhered to when using the Media and Printer combination defined in Section 1 of this document:

2.2. Printer Settings

Use the following settings on the printer:

- [Media Type] USERTYPE6
- [Media Weight] Printer Setting
- [Additional Setting] Paper Color Setting -1
- [Feeding Tray] MP Tray
- [Output Tray] Rear Output Tray
- [Paper Size] A4 Long Edge Feed

If you need to improve mis-registration, please try the following setting on the printer:

- [Media Type] USERTYPE14
- [Media Weight] Printer Setting
- [Additional Setting] Paper Color Setting -1

2.3. Custom Media Files

Use the following Custom Media File (CMF):

- [CMF Version] 01.E1.01
- [Media Type] USERTYPE6

Use the following Custom Media File (CMF) for durable toward scratch:

- [CMF Version] 02.E1.02
- [Media Type] USERTYPE14

2.4. General Printing Conditions

Please note the following general printing conditions when using this Media:

- Media must be fanned before loading into the tray.
- The Printing environment should be as close as possible to a standard office environment as low temperature might affect the fusing
- When you are not using the paper, it is recommended to store it in a plastic bag and in a flat place so that it is not affected by temperature and humidity.
- Due to the coating and surface smoothness of the Media, to prevent deterioration of Print Quality only print up to 10 sheets continuously.

3. Warranty

3.1. Summary

OKI's Standard warranty will apply for the Printer when this Media is being used except for the conditions set out in Section 3.2 below. Details on OKI's Standard Warranty can be found at the following link: https://www.oki.com/uk/printing/images/OKI_Warranty_Booklet_tcm67-47787.pdf.

3.2. Specific Issues with Media and Exclusions from Warranty

The following sections details the specific conditions and exclusions to Warranty when using the Media on the Printer:

- The life of certain parts and consumables will be reduced by use of the Media with the Printer. The warranty on these parts and consumables will be reduced as set out in the Table below:

| Item | Warranty |
|-------|---|
| Fuser | Standard yield of 100,000 images (based on an average of three simplex A4 pages per print job, long edge feed) will be reduced to 50,000 images. Even if Fuser still shows on the Printer Configuration page as having a percentage remaining, print quality may reduce. Warranty on the Fuser will therefore be either three months from date of purchase (see standard warranty statement) or the reduced yield whichever occurs first. |
| Drum | Standard yield of 30,000 images (based on an average of three simplex A4 pages per print job, long edge feed) will be reduced to 15,000 images. Even if Drum still shows on the Printer Configuration page as having a percentage remaining, print quality may reduce. Warranty on the Drum will therefore be either three months from date of purchase (see standard warranty statement) or the reduced yield whichever occurs first. |
| Belt | Standard yield of 80,000 images (based on an average of three simplex A4 pages per print job, long edge feed) will be reduced to 40,000 images. Even if Belt still shows on the Printer Configuration page as having a percentage remaining, print quality may reduce. Warranty on the Belt will therefore be either three months from date of purchase (see standard warranty statement) or the reduced yield whichever occurs first. |

| | |
|-----------------------|--|
| Paper Feed Roller set | The yield of the Paper Feed Roller set will reduce to 20,000 pages (based on average of three simplex A4 pages per print job, long edge feed) due to the surface property of the Media. Print jams may increase when this reduced life is reached resulting in a need to change the roller set. Warranty on the Paper Feed Roller set will therefore be either the standard warranty period (see standard warranty statement) or the reduced yield whichever occurs first. |
|-----------------------|--|

- Media must be printed from the MP Tray only and exit to the Top output tray.
- Only place one sheet at a time in the tray. If you do not do this you may get multiple feeds or mis-feeding of the media.
- We recommend taking sheets one by one from the output tray otherwise the media may fall from the output tray.
- The sharp horizontal line or white spread may occur. This phenomenon is affected and changing by operating environment.
- Print quality may not be as good around the perforations.
- If the image being printed goes across the perforation “dirty print” may occur on the printed output. This is caused by excess toner in the perforation which has not been fused to the perforated hole.
- Colour density, especially on solid patterns, may not be reduced and appear lighter.
- After printing on this Media, vertical lines or dirty print may occur. If your printout has these issues, please do not use the printer for a few hours and it may recover so that this issue no longer appears.
- Other conditions of use may also affect the limited life of the parts and consumables set out in the table above. Warranty claims are therefore always subjected to a detailed examination.